

55, Adelaide Street
Suite # 410
Toronto, Ontario, M5C 1K6



Tel: 800-360-8006
Fax : 416-361-1333
www.elororesources.com

ELORO RESOURCES LTD

HURDMAN - ASSAYS RESULTS

| Hole ID | From (m) | To (m) | Interval (m) | Zn % | Ag (g/t) |
|-----------|------------------|--------|--------------|--------|----------|
| ELO-06-01 | 85.75 | 97.40 | 11.65 m | 3.70% | 7.71 g/t |
| | Including | | | | |
| | 88.30 | 97.40 | 9.10 m | 4.21% | 8.72 g/t |
| | Including | | | | |
| | 85.75 | 86.45 | 0.70 m | 6.269% | 8 g/t |
| | 89.20 | 91.55 | 2.35 m | 5.97% | 16.2 g/t |
| | 89.20 | 90.35 | 1.15 m | 7.647% | 30 g/t |
| | 93.50 | 97.40 | 3.9 m | 5.36% | 2.64 g/t |
| | 93.50 | 94.15 | 0.65m | 7.956% | 3 g/t |
| | 95.70 | 97.40 | 1.70m | 7.566% | 4 g/t |

| Hole ID | From (m) | To (m) | Interval (m) | Zn % | Ag (g/t) |
|-----------|------------------|--------|--------------|-----------|----------|
| ELO-06-02 | 79.25 | 85.45 | 6.20 m | 1.63% | 4.84 g/t |
| | Including | | | | |
| | 80.35 | 85.45 | 5.1 m | 1.85% | 5.45 g/t |
| | 80.35 | 82.15 | 1.8 m | 3.15% | 2.55 g/t |
| | Including | | | | |
| 89.55 | 91.00 | 1.45 m | 3.57% | 13.41 g/t | |

| Hole ID | From (m) | To (m) | Interval (m) | Zn % | Ag (g/t) |
|-----------|------------------|--------|--------------|-------|-----------|
| ELO-06-03 | 81.80 | 84.15 | 2.30 m | 2.51% | 9.20 g/t |
| | Including | | | | |
| | 82.40 | 83.00 | 0.6 m | 5.54% | 14.00 g/t |
| | 86.75 | 88.45 | 1.7 m | 1.62% | 21.65 g/t |

| Hole ID | From (m) | To (m) | Interval (m) | Zn % | Ag (g/t) |
|-----------|------------------|--------|--------------|--------|------------|
| ELO-06-04 | 60.10 | 71.40 | 11.30 m | 2.09% | 39.56 g/t |
| | Including | | | | |
| | 60.10 | 60.60 | 0.50 m | 10.41% | 11.00 g/t |
| | 65.55 | 68.25 | 2.70 m | 3.43% | 101.80 g/t |

| Hole ID | From (m) | To (m) | Interval (m) | Zn % | Ag (g/t) |
|-----------|------------------|--------|--------------|-------|-----------|
| ELO-06-05 | 57.10 | 66.60 | 9.50 m | 1.51% | 8.10 g/t |
| | Including | | | | |
| | 58.35 | 59.85 | 1.5 m | 4.45% | 12.67 g/t |
| | 64.20 | 64.80 | 0.6 m | 3.49% | 13.00 g/t |
| | 65.95 | 66.60 | 0.65 m | 3.92% | 27.00 g/t |

| Hole ID | From (m) | To (m) | Interval (m) | Zn % | Ag (g/t) |
|-----------|------------------|--------|--------------|--------|-----------|
| ELO-06-06 | 38.80 | 59.50 | 20.70 m | 2.08% | 9.51 g/t |
| | Including | | | | |
| | 51.75 | 54.50 | 2.75 m | 4.82% | 5.64 g/t |
| | Including | | | | |
| | 56.95 | 59.50 | 2.55 m | 4.13% | 17.47 g/t |
| | 81.10 | 84.50 | 4.40 m | 0.95% | 11.14 g/t |
| | Including | | | | |
| | 84.20 | 84.50 | 0.30 m | 5.636% | 34 g/t |

| Hole ID | From (m) | To (m) | Interval (m) | Zn % | Ag (g/t) |
|-----------|------------------|--------|--------------|-----------|-----------|
| ELO-06-07 | 31.65 | 45.80 | 14.15 m | 1.22% | 2.22 g/t |
| | Including | | | | |
| | 31.62 | 37.05 | 5.40 m | 1.93% | 2.41 g/t |
| | Including | | | | |
| | 45.30 | 45.80 | 0.50 m | 4.90% | 7.00 g/t |
| | Including | | | | |
| | 62.50 | 70.40 | 7.90 m | 2.48% | 10.43 g/t |
| | Including | | | | |
| | 66.00 | 66.35 | 0.35 m | 5.11% | 3.20 g/t |
| | 67.10 | 70.40 | 3.30 m | 3.58% | 18.25 g/t |
| | 67.10 | 67.80 | 0.70 m | 6.1% | 8.80 g/t |
| | Including | | | | |
| 73.25 | 74.90 | 1.65 m | 1.01% | 42.90 g/t | |

| Hole ID | From (m) | To (m) | Interval (m) | Zn % | Ag (g/t) |
|-----------|------------------|--------|--------------|-------|-----------|
| ELO-06-08 | 52.25 | 80.50 | 28.25 m | 2.79% | 20 g/t |
| | Including | | | | |
| | 64.45 | 66.20 | 1.75 m | 7.11% | 50.42 g/t |
| | 69.50 | 79.15 | 9.65 m | 4.45% | 24.95 g/t |
| | 71.25 | 79.15 | 7.90 m | 5.22% | 28.02 g/t |
| | 71.25 | 73.25 | 2.00 m | 7.60% | 45.00 g/t |

| Hole ID | From (m) | To (m) | Interval (m) | Zn % | Ag (g/t) |
|-----------|------------------|--------|--------------|-------|-----------|
| ELO-06-09 | 48.40 | 67.25 | 18.85 m | 1.71% | 4.90 g/t |
| | Including | | | | |
| | 58.90 | 60.60 | 1.70 m | 3.89% | 7.74 g/t |
| | 62.05 | 67.25 | 5.20 m | 2.44% | 6.19 g/t |
| | 62.05 | 64.30 | 2.25 m | 3.56% | 10.12 g/t |

| Hole ID | From (m) | To (m) | Interval (m) | Zn % | Ag (g/t) |
|-----------|------------------|--------|--------------|--------|-----------|
| ELO-06-12 | 39.20 | 46.50 | 7.30 m | 4.99% | 26.57 g/t |
| | Including | | | | |
| | 39.20 | 43.90 | 4.70 m | 7.07% | 30.60 g/t |
| | 39.20 | 42.85 | 3.65 m | 8.55% | 35.59 g/t |
| | 40.50 | 40.80 | 0.30 m | 25.83% | 16.40 g/t |
| | Including | | | | |
| | 52.35 | 58.50 | 6.15 m | 3.48% | 15.46 g/t |
| | Including | | | | |
| | 55.70 | 56.70 | 1.00 m | 5.66% | 10.10 g/t |
| | 57.00 | 57.35 | 0.35 m | 9.26% | 24.50 g/t |

55, Adelaide Street
Suite # 410
Toronto, Ontario, M5C 1K6



ELORO RESOURCES LTD

Tel: 800-360-8006
Fax : 416-361-1333
www.elororesources.com

HURDMAN - GOLD RESULTS

| Hole ID | From (m) | To (m) | Interval (m) | Au g/t | Ag | Zn % |
|----------------|------------------|--------|--------------|--------|--------|-------|
| ELO-06-03 | 83.00 | 83.40 | 0.40 | 5.10 | 3.00 | 0.02 |
| ELO-06-04 | 66.65 | 68.80 | 2.15 | 0.88 | 102.80 | 2.60 |
| | Including | | | | | |
| | 68.25 | 68.80 | 0.55 | 1.32 | 76.00 | 0.09 |
| ELO-06-06 | 60.90 | 61.35 | 0.45 | 1.31 | 18.00 | 0.50 |
| | 79.80 | 80.10 | 0.30 | 1.99 | 39.00 | 0.31 |
| ELO-06-07 | 74.90 | 75.35 | 0.45 | 1.95 | 13.20 | 0.189 |
| | 75.35 | 76.20 | 0.85 | 1.18 | 13.60 | 0.43 |
| | 78.85 | 79.35 | 0.40 | 1.15 | 21.00 | 0.58 |
| ELO-06-08 | 72.00 | 76.40 | 4.40 | 1.97 | 34.02 | 4.00 |
| ELO-06-10 | 52.70 | 53.50 | 0.80 | 1.28 | 14.50 | 0.62 |
| ELO-06-11 | 42.95 | 44.60 | 2.15 | 1.73 | 16.22 | 0.34 |
| | 43.70 | 45.10 | 1.40 | 2.40 | 19.46 | 0.34 |
| | Including | | | | | |
| | 43.70 | 44.15 | 0.45 | 5.97 | 46.00 | 0.35 |
| | 60.50 | 61.00 | 0.50 | 3.39 | 52.40 | 0.14 |
| | 64.30 | 65.80 | 1.50 | 1.17 | 24.00 | 0.57 |
| ELO-06-12 | 39.20 | 41.35 | 2.15 | 1.37 | 57.68 | 10.36 |
| | Including | | | | | |
| | 39.20 | 39.80 | 0.6 | 2.05 | 191.00 | 7.31 |
| | 40.50 | 41.35 | 0.85 | 2.00 | 8.12 | 13.87 |
| | 58.50 | 58.95 | 0.45 | 48.69 | 166.00 | 0.41 |
| | 58.50 | 58.95 | 0.45 | 51.98 | | |
| Average | | | 0.45 | 50.34 | | |